

Part No. **43323**

# USB 3.2 TYPE C LAPTOP MINI DOCK - 4K HDMI & DP, PD 3.0 100W, USB 3.2, GIGABIT ETHERNET, SD, AUDIO

CONNECT YOUR PERIPHERALS VIA A SINGLE USB TYPE C CABLE



## DESCRIPTION

- Adds 2 USB Type A ports & 1 USB Type C port (5Gbps), a 4K HDMI and DP port, Gigabit Ethernet and an Audio port to a laptop
- Supports 3840x2160@30Hz for an HDMI or DP display and Full HD 1920x1080 for simultaneous use of HDMI and DP displays
- Features DisplayPort Alternate Mode
- USB Power Delivery 3.0 (100W) allows charging the laptop while using the Mini Dock
- 2 year warranty

## RELATED PRODUCTS

0

The Lindy USB 3.2 Type C Mini Laptop Dock is a compact and versatile solution for connecting laptops to a range of interfaces including displays. Featuring all critical interfaces required for a modern workstation, this Mini Dock uses a single USB 3.2 Type C cable to connect up to two displays, while improving connectivity to other devices through Gigabit Ethernet, USB 3.2 / 3.1 Gen 1 / USB 3.0 SuperSpeed and SD card ports. It also features an Audio port for connection of a headphone or microphone.

The Mini Dock enables the connection of a display to a laptop via HDMI or Displayport at resolutions of 3840x2160@30Hz or of both simultaneously using DisplayPort Alternate Mode through the USB Type C port. It features a combined USB Type C data & power port which supports Power Delivery up to 100W while also transmitting data at up to 5Gbps. Power delivery 3.0 supports bidirectional power up to almost 100 Watt and enables higher voltage and current values to be negotiated between the connected devices - host or peripherals. The two integrated USB Type A ports provide up to 5Gbps of data transfer, perfect for connecting Type A peripherals such as a hard drive, printer or webcam. The right USB port also supports the USB Battery Charging Specification 1.2 for charging mobile devices, which is able to deliver 5V and up to 1.5A for faster charging compared to a standard USB port.

# USB 3.2 TYPE C LAPTOP MINI DOCK - 4K HDMI & DP, PD 3.0 100W, USB 3.2, GIGABIT ETHERNET, SD, AUDIO

## SPECIFICATIONS

<b>Interface</b>	USB Type C to 1x HDMI / 1x DP / 1x RJ45 / 2x USB Type A / 1x USB Type C / 1x SD / 1x Audio
<b>Interface Standard</b>	USB 3.2 / 3.1 Gen 1 / USB 3.0, HDMI 1.4, DP 1.2, Gigabit LAN, Audio (combo)
<b>Supported Bandwidth</b>	5 Gbps, 10/100/1000Mbps
<b>Maximum Input Resolution</b>	3840x2160@30Hz
<b>Maximum Output Resolution</b>	3840x2160@30Hz (HDMI), 3840x2160@30Hz (DP) simultaneous connection: 1920x1080
<b>Chipset</b>	VM3332, VL817, VL102, AU6438, RTL8153B, HS-100B
<b>Compatibility</b>	USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support
<b>Power Delivery</b>	PD 3.0 up to 100W (20V 5A)
<b>HDCP Support</b>	HDCP 1.4
<b>Supported Audio</b>	Supports 48/44.1kHz audio
<b>Seperate Audio Ports</b>	1x Audio combo port 3.5mm
<b>Special Features</b>	DisplayPort Alternate Mode, USB Type C Female port supports power and data, 1x Battery Charging 1.2 port

## CONNECTORS

<b>Input</b>	1 x USB Type C (Male)
<b>Output</b>	1x HDMI (Female), 1x DisplayPort (Female), 1x RJ45 (Female), 2x USB Type A (Female), 1x USB Type C (Female) / 1x SD slot, 1x 3.5mm Audio (Female)
<b>Power</b>	1 x USB Type C (Female) PD port

## PHYSICAL PROPERTIES

<b>Dimensions (approx.) WxDxH</b>	116.5x61x16mm (4.59x2.4x0.63in)
<b>Housing Material</b>	Aluminium
<b>Net Weight</b>	0.115kg (0.25lb)
<b>Operating Temperature</b>	0°C - 55°C (32°F - 131°F)
<b>Storage Temperature</b>	-10°C - 70°C (14°F - 158°F)
<b>Humidity</b>	0 - 85% RH (non-condensing)
<b>Power Requirements</b>	Bus-powered
<b>Colour</b>	Grey

## MISCELLANEOUS

<b>Packaging Type</b>	Carton Box
<b>Packaging Dimension</b>	150x137x120mm (5.91x5.39x0.79in)
<b>Gross Weight</b>	0.15kg (0.33lb)
<b>Warranty (Years)</b>	2
<b>Certificated</b>	CE, UKCA, FCC, REACH & RoHS, CP65

## PURCHASING INFORMATION

<b>No.</b>	43323
<b>EAN</b>	4002888433235

## PACKAGING CONTENTS

USB 3.2 Type C Laptop Mini Dock  
Lindy Manual