

Part No. **38150**

4 PORT HDMI MULTI-VIEW SWITCH



DESCRIPTION

- Integrates 4 Full HD 1080p signals for display on a single HDMI display
- Supports 4 viewing modes; Quadview, Picture & Picture, Dual Video and Standard
- Seamless switching between inputs/viewing modes
- Independent switching of audio and video signals
- 2 Year warranty

This HDMI 4x1 Multi-View Switch is a high performance video switch which allows signals from four different Full HD sources to be integrated for simultaneous display on a single monitor. Featuring four different viewing modes [Quad-View, Full Screen, Picture and Picture & Dual Video] the Multi-view switch allows for the monitoring of multiple video sources in different viewing configurations to meet the requirements of standard installations.

To ensure optimal performance in mission critical environments the Switch provides seamless switching, ensuring that there is no frame loss whilst switching between the connected source devices or between different picture modes.

Full HD 1080p resolutions are supported on both the input and output for simple integration within typical business environments, whilst the output can be down-scaled to 720p for operation with legacy displays.

Switching between audio and video channels can be completed independently using either the supplied remote control or using the front panel buttons. This independent switching allows a single audio source to be used continuously whilst switching between the connected source devices or conversely a single video source to be monitored whilst the audio source is switched.

This flexible, cost effective switch has been designed to be used in a number of different applications, such as:

- Digital Presentation
- CCTV Surveillance & Control
- Conference & Meeting Room

RELATED PRODUCTS

0

4 PORT HDMI MULTI-VIEW SWITCH

SPECIFICATIONS

AV Interface	HDMI
Interface Standards	HDMI 1.3a
Supported Bandwidth	4.95Gbps
Maximum Resolution	1920x1080@60Hz 4:4:4 8bit
HDCP Support	1.2
Supported Audio	Audio Pass-through
Separate Audio Ports	-
IR Support	-
CEC Support	-
Serial Interface	-
Special Features	PiP, PaP, Independent audio switching

PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH	190x90x23mm (7.48x3.54x0.91in)
Housing Material	Metal
Net Weight	0.85kg (1.88lb)
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	20%-90% RH (non-condensing)
Power Requirements	12VDC 2A
Colour	Black

CONNECTORS

Input	4 x HDMI (Female)
Output	HDMI (Female)
Control	-
Power	5.5/2.1mm DC socket

MISCELLANEOUS

Packaging Type	Carton box
Packaging Dimension	200x170x60mm (7.87x6.69x2.36in)
Gross Weight	1.017kg (2.24lb)
Warranty (Years)	2
Certificated	CE, UKCA, FCC, RoHS & REACH

PURCHASING INFORMATION

No.	38150
EAN	4002888381505

PACKAGING CONTENTS

HDMI 4x1 Multi-view Switch
 IR Remote control with CR2025 battery
 Multi-Country Power Supply (EU, UK, US & AUS)
 Lindy Manual