

Part No. **38225**

HDMI OVER POWERLINE EXTENDER, TRANSMITTER

EXTEND HDMI SIGNALS VIA POWER LINE TRANSMISSION

DESCRIPTION

Extends HDMI signals over a single powerline circuit
Transmit content to 3 compatible receivers, as well as to a local HDMI display
Supports resolutions up to Full HD 1920x1080@60Hz
Receive IR signals from the display side of the setup
2 year warranty

HDMI over Powerline extenders provide a useful solution for extending HDMI content to one or more displays within one electrical circuit.

The Lindy HDMI over Powerline Transmitter is one part of a high-quality solution for extending HDMI content from a source device to a display using a single electrical power circuit. Combined with the compatible receiver unit, this extender provides simple, hassle-free content distribution within small office, store front or residential setups.

Supporting resolutions up to 1920x1080@60Hz ensuring excellent Full HD quality for the user. This device is ideal for sharing video and audio content into bedrooms, home offices or small-scale digital signage using pre-existing electrical wiring.

An HDMI loop-out allows for connection of a local HDMI display, while connection to 3 compatible receivers allows for larger scale distribution to multiple displays. A 3.5mm IR connection also allows for simple control from the display side of the setup.

RELATED PRODUCTS

0

HDMI OVER POWERLINE EXTENDER, TRANSMITTER

SPECIFICATIONS

AV Interface	HDMI
Interface Standard	1.3
Supported Bandwidth	6.75Gbps
Maximum Distance	-
Maximum Resolution	1920x1080@60Hz 4:4:4 8bit
HDCP Support	1.4
EDID Pass Through	Pass-through
Supported Audio	LPCM 2CH
Separate Audio Ports	-
IR Support	20-60kHz
CEC Support	-
Serial Interface	-
Transmission Protocol	-
Transmission Medium	IEC
Laser Class (only for Fibre)	-
Wavelength (only for Fibre)	-
Chipset	ITE
Special Features	Output to 3 Receivers HDMI Local Loop Out

PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH	135x29x96.5mm (5.31x1.14x3.8in)
Housing Material	Metal
Net Weight	0.405kg (0.89lb)
Operating Temperature	32°C - 104°C (90°F - 219°F)
Storage Temperature	-4°C - 104°C (25°F - 219°F)
Humidity	20 -90% RH (non-condensing)
Power Requirements	100-240 VAC
Colour	Black

CONNECTORS

Transmitter Input	HDMI Type A (Female)
Transmitter Output	HDMI Type A (Female) 3.5mm IR (Female) IEC C6 (Male)
Receiver Input	-
Receiver Output	-
Bi-directional Ports	-
Power	IEC C6 (Male)

MISCELLANEOUS

Packaging Type	Carton Box
Packaging Dimension	262x80x150mm (10.31x3.15x5.91in)
Gross Weight	0.732kg (1.61lb)
Warranty (Years)	2
Certificated	CE, FCC, RoHS, REACH & California Proposition 65

PURCHASING INFORMATION

No.	38225
EAN	4002888382250

PACKAGING CONTENTS

HDMI over Powerline Extender, Transmitter
IR Emitter Cable, 1.5m
Multi-country C5 Power Cables (UK, EU, US & AUS)
Lindy Manual