LINDY
CONNECTION PERFECTION

Part No. **38235**

2 PORT HDMI 2.0 18G SPLITTER

DESCRIPTION

· Split a single HDMI 2.0 source across 2 HDMI displays
· Supports resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
· HDCP 2.2 support for enhanced compatibility
· EDID Management for hassle free installation
· 2 Year Warranty

The Lindy 2 Port HDMI 2.0 18G Splitter is a compact, high quality solution for distributing HDMI 2.0 18G signals across dual displays from one source device. With support for resolutions up to 4K 60Hz 4:4:4 8bit, this splitter is great for creating eye-catching digital signage in retail scenarios, showing high quality video in different rooms in medical facilities or ensuring audiences do not miss any of the action in dual display sports bars. Additional support for High-Dynamic Range ensures video content can be seen with enhanced brightness, superior contrasts and a much wider colour gamut, for more lifelike colour.

The additional ability to cascade this splitter up to three further levels allows for an extended HDMI splitting experience, ideal for multi-screen situations such as informational broadcasting in airports, train stations or stock exchange offices.

HDCP 2.2 support ensures there are no issues with a variety of 4K content when connected to source devices including set top boxes, Blu-Ray players and 4K HDR media players, while a smart EDID management switch on the unit provides maximum compatibility with the display.
The splitters durable, compact design also ensures the unit can be installed discreetly, ensuring there is no distraction from the content on screen.

RELATED PRODUCTS

0

2 PORT HDMI 2.0 18G SPLITTER

LINDY
CONNECTION PERFECTION

SPECIFICATIONS

AV Interface	HDMI
Interface Standards	HDMI 2.0
Supported Bandwidth	18Gbps
Maximum Resolution	3840x2160@60Hz 4:4:4 8bit
HDCP Support	2.2
Supported Audio	Audio Pass-through
Separate Audio Ports	-
CEC Support	-
Serial Interface	-
Special Features	EDID emulation

CONNECTORS

Input	1 x HDMI (Female)
Output	2 x HDMI (Female)
Control	-
Power	5.5/2.1mm DC socket

MISCELLANEOUS

Packaging Type	Carton box
Packaging Dimension	146x65x105mm (5.75x2.56x4.13in)
Gross Weight	0.342kg (0.75lb)
Warranty (Years)	2
Certificated	CE, UKCA, FCC, RoHS, REACH & California Proposition 65

PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH	100x56x16mm (3.94x2.2x0.63in)
Housing Material	Metal
Net Weight	0.263kg (0.58lb)
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	20 - 90% RH (Non-condensing)
Power Requirements	5VDC 1A
Colour	Black

PURCHASING INFORMATION

No.	38235
EAN	4002888382359

PACKAGING CONTENTS

HDMI Splitter
Multi-country PSU (UK, EU, US & AUS)
Lindy Manual